AT-120X-S, 850nm
XLR Series IR Illuminators
Data Sheet

AXTON
ILLUMINATE THE NIGHT

AT-120X-S with I/O Ports & Day/Night Switch

- I/O Ports for seamless & precise cameras synchronization
- Built-in Low Voltage Power Supply - no additional equipment to install
- Pannels come pre-connected via junction box
- Built-in Day/Night Switch
- Remote Control via Web Server (additional equipment is required)

Made in the USA

- All illuminators designed and built in Salt Lake City, UT, USA

Lifetime Warranty with Advanced Replacement

- We value your trust, that's why all products are covered by a lifetime warranty with advanced replacement

TECHNICAL SPECIFICATIONS

Wavelength:	850nm (semi-covert)
Input Voltage:	24V DC
Power Consumption:	120 W
Operating Temperature:	-40°F...+122°F/-40°C...+52°C
Dimensions:	11" x 7" x 2.5" /280 x 178 x 64 mm
Weight	7 lb. / 3 kg.
Environmental	IP 67



ILLUMINATION DISTANCE



ANGLE	RANGE	HFOV
10°	930'/280m	194'/58m
30°	620'/188m	320'/97m
60°	413'/125m	374'/113m
130°	235'/70m	420'/127m

AXTON 801 W. Robinson Dr., Suite #500, North Salt Lake, UT 84054 T +1-801-519-0500 F +1-801-519-0501 www.axtontech.com sales@axtontech.com